

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 38 NRO
LI/SS	171 D

Dimensions International Standard

Section Width (mm)	708
Overall Diameter (mm)	1820
Static Loaded Radius (mm)	794
Rolling Circumference (mm)	5447
SRI (mm)	875
Rim Rec	DW 25 B
Rim Alt	DW 23 B
Narrow Rim option	DW 23 B
ECE	E11-106R-004520
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
70	3075	3580	4080	4585	5090	5595
from 65 to 40	3380	3935	4485	5040	5595	6150
30	3445	4010	4570	5140	5705	6270
20	3515	4090	4660	5240	5815	6395
10	3715	4325	4930	5540	6150	6765
*Upto 10 Cyc with front loader	4730	5505	6275	7055	7830	8610
10HT	3445	4010	4570	5140	5705	6270

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/19/2024 12:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..