

MULTIMAX MP 522 - Technical Specifications



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler
Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	480/80 R 26 IND
LI/SS	160 A8/B

Dimensions US Standard

Usa code	94052707
Section Width (inch)	18.9
Overall Diameter (inch)	56.2
Static Loaded Radius (inch)	25.1
Rolling Circumference (inch)	168.8
Rim Rec	DW 15 L
Rim Alt	DW 16 L
ECE	E11-106R-002970

Load capacity (lbs)

mph / psi	23	29	32	35	38	41	44	46	49	52
30	5750	6750	7340	7840	8330	8830	9420	9920	-	-
25	5750	6750	7340	7840	8330	8830	9420	9920	-	-
20	6160	7220	7860	8390	8920	9460	10090	10610	-	-
15	6390	7500	8160	8710	9260	9810	10470	11010	-	-
5 Cvc.	7000	8630	9380	10120	11010	11760	12500	13390	14140	14880
Static	10720	13240	14380	15520	16890	18030	19170	20530	21680	22820

Printed on 5/19/2024 1:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..