

RIDEMAX IT 697 (M+S) - Technical Specifications



Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	600/65 R 28 IND
LI/SS	165 A8/160 D

Dimensions US Standard

Usa code	94066995
Section Width (inch)	23.3
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	177.5
Rim Rec	W 18 L
Rim Alt	DW 20 B
ECE	E11-106R-006760

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	4860	5950	6550	7840	8830	9920
30	5260	6440	7080	8470	9550	10710
25	5570	6810	7500	8970	10110	11350
20	5840	7140	7860	9410	10600	11900

Printed on 5/18/2024 6:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..