

AGRIMAX FORCE - Technische Daten



Description

AGRIMAX FORCE, das Spitzenprodukt von BKT, ist ein Radialreifen, der speziell zur Bodenbearbeitung, sowie Transport- und Ernteanwendungen mit Hochleistungstraktoren und Erntemaschinen entwickelt wurde. Dabei bietet er ein hervorragendes Arbeitspotenzial sowie effiziente Leistungen. Dank der IF-Technologie kann dieser Reifen schwere Lasten bei geringerem Reifendruck im Vergleich zu einem Standardreifen bei reduzierter Bodenverdichtung tragen. AGRIMAX FORCE hat einen verstärkten Wulst und wartet mit erstklassiger Traktion, ausgezeichneten Selbstreinigungseigenschaften und Kraftstoffersparnis neben einem komfortablen Fahrerlebnis auf.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Erntemaschine • Hochleistungstraktor

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | IF 480/95 R 50 |
| LI/SS | 170 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94058006 |
| Section Width (inch) | 18.9 |
| Overall Diameter (inch) | 85.4 |
| Static Loaded Radius (inch) | 39.4 |
| Rolling Circumference (inch) | 258.8 |
| Rim Rec | DW 16 B |
| ECE | E11-106R-004898 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-------------------------------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5650 | 6490 | 7460 | 8420 | 9380 | 10350 | 11310 | 12040 |
| From 40 to 25 | 6220 | 7140 | 8200 | 9260 | 10320 | 11380 | 12430 | 13200 |
| 20 | 6460 | 7420 | 8520 | 9620 | 10720 | 11830 | 12930 | 13760 |
| 12 | 6710 | 7700 | 8850 | 10000 | 11130 | 12280 | 13430 | 14290 |
| 5 | 7890 | 9060 | 10410 | 11750 | 13090 | 14440 | 15780 | 16800 |
| *Upto 5 Cyc with front loader | 8700 | 10000 | 11470 | 12960 | 14440 | 15920 | 17400 | 18520 |
| 5HT | 6460 | 7420 | 8520 | 9620 | 10720 | 11830 | 12930 | 13760 |

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 18.05.2024 21:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..