

AGRIMAX RT 600 - Technische Daten

Description

AGRIMAX RT 600 ist der ideale Reifen für Grasflächen sowie Ernte- und Spritzanwendungen. Mit seiner breiten Aufstandsfläche bietet AGRIMAX RT 600 eine optimale Druckverteilung auf dem Boden, reduziert den Schaden von Grasland und schützt den Boden. Dank der abgerundeten Schulterstruktur, dem verstärkten Wulst und der größeren Stollenzahl gewährleistet er ausgezeichnete Stabilität und Traktion.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Erntemaschine • Streumaschine • Traktor



| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 900/60 R 32 |
| LI/SS | 181 A8/178 B |

Dimensions International Standard

| | |
|----------------------------|-------------------|
| Section Width (mm) | 896 |
| Overall Diameter (mm) | 1893 |
| Static Loaded Radius (mm) | 841 |
| Rolling Circumference (mm) | 5697 |
| SRI (mm) | 900 |
| Rim Rec | DW 27 B |
| Rim Alt | DW 28 B ; DW 30 B |
| ECE | E11-106R-005768 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.4 | 3.8 |
|------------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 50 | 3375 | 3825 | 4350 | 4800 | 5325 | 5925 | 6375 | 6975 | 7500 | - | - |
| 40 | 3715 | 4210 | 4785 | 5280 | 5860 | 6520 | 7015 | 7675 | 8250 | - | - |
| 30 | 3975 | 4505 | 5125 | 5655 | 6270 | 6980 | 7510 | 8215 | 8830 | - | - |
| 10 LT | 4975 | 5640 | 6415 | 7080 | 7850 | 8735 | 9400 | 10285 | 11055 | - | - |
| 10 HT | 3975 | 4505 | 5125 | 5655 | 6270 | 6980 | 7510 | 8215 | 8830 | - | - |
| 10 Cyc. | - | 6765 | 7690 | 8485 | 9415 | 10475 | 11270 | 12330 | 13255 | 13465 | 14025 |

Printed on 19.05.2024 18:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..