

## AGRIMAX RT 600 - Technische Daten

### Description

AGRIMAX RT 600 ist der ideale Reifen für Grasflächen sowie Ernte- und Spritzanwendungen. Mit seiner breiten Aufstandsfläche bietet AGRIMAX RT 600 eine optimale Druckverteilung auf dem Boden, reduziert den Schaden von Grasland und schützt den Boden. Dank der abgerundeten Schulterstruktur, dem verstärkten Wulst und der größeren Stollenzahl gewährleistet er ausgezeichnete Stabilität und Traktion.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Erntemaschine • Streumaschine • Traktor



Version	STANDARD
Type	TL
Tyre Size	IF 680/85 R 32 CFO
LI/SS	179 D

## Dimensions US Standard

Usa code	94065486
Section Width (inch)	26.9
Overall Diameter (inch)	77.2
Static Loaded Radius (inch)	33.3
Rolling Circumference (inch)	230.7
Rim Rec	DW23 B
Rim Alt	DW21 B
ECE	E11-106R-006401

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
From 40 to 25	8020	9230	10590	11960	13330	14690	16060	17100
20	8340	9590	11010	12430	13860	15280	16700	17770
12	8660	9950	11430	12910	14380	15860	17340	18450
5	10180	11710	13450	15180	16920	18650	20390	21690
Upto 20 Cyc	10430	11990	13770	15540	17320	19090	20880	22210
Upto 10 Cyc	12430	14300	16410	18530	20650	22770	24890	26480
5 HT	8340	9590	11010	12430	13860	15280	16700	17770

Printed on 19.05.2024 15:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..