

AT 625 - Datenblatt



Description

AT 625 eignet sich für Baggerlader und Kompaktlader bei allen Bagger- und Ladearbeiten in der Landwirtschaft. Die extra tiefe Lauffläche steht für verstärkte Durchstichfestigkeit und Beständigkeit. AT 625 zeichnet sich durch ausgezeichnete Traktion und Stabilität sowie verbesserte Schnitt- und Reißfestigkeit aus.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Baggerlader • Kompaktlader

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
14.9 - 24	STANDARD	94051007	R4	145 A8	12	DW 13	DW 11 ; DW 12 ; DW 13 L	15.7	49.8	22.6	149.6	TL
14.9 - 24	STANDARD	94041367	R4	145 A8	12	DW 13	DW 11 ; DW 12 ; DW 13 L	15.7	49.8	22.6	149.6	TT
16.9 - 28	INDUSTRIAL	94051076	R4	152 A8	12	DW 15 L	DW 14 L	17.7	55.7	25.4	167.5	TL
16.9 - 28	INDUSTRIAL	94040315	R4	152 A8	12	DW 15 L	DW 14 L	17.7	55.7	25.4	167.5	TT
16.9 - 28	SPECIAL	94055470	R4	152 A8	12	DW 15 L	DW 14 L	17.7	55.7	25.4	167.5	TT

Printed on 22.05.2024 19:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..