

EARTHMAX SR 35 - Datenblatt



Description

Earthmax SR 35 ist ein radialer All Steel Niederquerschnittsreifen, der speziell für knickgelenkte Muldenkipper und Radlader entworfen wurde. Er eignet sich vortrefflich für Arbeiten, die hervorragende Traktion und Flotation erfordern. Dank der robusten Karkasse mit Stahlbändern verleiht der Reifen außergewöhnliche Dauerhaftigkeit sowie Widerstandsfähigkeit gegenüber Rissen und Stichen.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Knickgelenkter Muldenkipper • Planierer • Radlader

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | TMPH |
|-----------------------------|------------------------|----------|----------|--------|--------------|------------|-----------------------|------|------|------|-------|------|------|
| 650/65 R 25 (25/65 R 25) | CUT RESISTANT COMPOUND | 94058587 | E3 | ** | 180 B | 19.50/2.5 | | 25 | 59 | 26.3 | 176.9 | TL | 138 |
| 650/65 R 25 (25/65 R 25) | CUT RESISTANT COMPOUND | 94058631 | E3/L3 | **/* | 180 B/193 A2 | 19.50/2.5 | | 25 | 59 | 26.3 | 176.9 | TL | 138 |
| 650/65 R 25 (25/65 R 25) | CUT RESISTANT COMPOUND | 94058624 | L3 | * | 193 A2 | 19.50/2.5 | | 25 | 59 | 26.3 | 176.9 | TL | 0 |
| 750/65 R 25 (30/65 R 25) | CUT RESISTANT COMPOUND | 94051786 | E3 | ** | 190 B | 24.00/3.0 | 22.00/3.0,25.00/3.0 | 29.1 | 63 | 28.1 | 189.1 | TL | 153 |
| 750/65 R 25 (30/65 R 25) | CUT RESISTANT COMPOUND | 94053636 | E3/L3 | **/* | 190 B/202 A2 | 24.00/3.0 | 22.00/3.0 ; 25.00/3.0 | 29.1 | 63 | 28.1 | 189.1 | TL | 153 |
| 750/65 R 25 (30/65 R 25) | CUT RESISTANT COMPOUND | 94071340 | L3 | ** | 209 A2 | 24.00/3.0 | 22.00/3.0,25.00/3.0 | 29.1 | 63 | 28.1 | 189.1 | TL | 0 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94064410 | E3/L3 | **/* | 195 B/206 A2 | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 151 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94064427 | E3 | ** | 195 B | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 151 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94064434 | L3 | * | 206 A2 | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 0 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94067589 | L3 | ** | 213 A2 | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 0 |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | 94059812 | E3/L3 | **/* | 203 B/214 A2 | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 35 | 73.2 | 32.1 | 218.9 | TL | 191 |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | 94059805 | E3 | ** | 203 B | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 35 | 73.2 | 32.1 | 218.9 | TL | 191 |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | 94059836 | L3 | * | 214 A2 | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 35 | 73.2 | 32.1 | 218.9 | TL | 0 |

Printed on 18.05.2024 19:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..