

EARTHMAX SR 41 - Technische Daten



Description

EARTHMAX SR 41 ist der ideale All-Steel-Radialreifen für Loder und Planierer im Transport- Lade und Planiereinsatz. Dank seiner All-Steel-Radialstruktur und dem speziellen Blockmuster verleiht EARTHMAX SR 41 erstklassige Schnittfestigkeit sowie ein langes Reifenleben. Neben langen Betriebsstunden ohne Maschinenstillstand bietet der Reifen außergewöhnlichen Komfort.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Knickgelenkter Muldenkipper • Planierer • Radlader
• flache Dumper

Version	STANDARD COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B

Dimensions International Standard

TKPH	285
Overall Width (mm)	761
Overall Diameter (mm)	1861
Static Loaded Radius (mm)	830
Rolling Circumference (mm)	5510
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	11500	11800	12500	12850	13600	14000

Printed on 19.05.2024 00:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..