

EARTHMAX SR 41 - Technische Daten



Description

EARTHMAX SR 41 ist der ideale All-Steel-Radialreifen für Loder und Planierer im Transport- Lade und Planiereinsatz. Dank seiner All-Steel-Radialstruktur und dem speziellen Blockmuster verleiht EARTHMAX SR 41 erstklassige Schnittfestigkeit sowie ein langes Reifenleben. Neben langen Betriebsstunden ohne Maschinenstillstand bietet der Reifen außergewöhnlichen Komfort.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Knickgelenkter Muldenkipper • Planierer • Radlader
• flache Dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	203 B/214 A2

Dimensions US Standard

Usa code	94059911
TMPH	164
Overall Width (inch)	34.6
Overall Diameter (inch)	73.4
Static Loaded Radius (inch)	33
Rolling Circumference (inch)	223.6
Rim Rec	27.00/3.50
Rim Alt	27.00/3.0, 28.00/3.5
Star Rating	**/*
TRA Code	E4/L4

Load capacity (lbs)

mph / psi	58	62	65	69
30	30900	31400	33300	34200
5	40800	43000	45400	46700

Printed on 18.05.2024 20:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..