

## EARTHMAX SR 41 - Datenblatt



### Description

EARTHMAX SR 41 ist der ideale All-Steel-Radialreifen für Loder und Planierer im Transport- Lade und Planiereinsatz. Dank seiner All-Steel-Radialstruktur und dem speziellen Blockmuster verleiht EARTHMAX SR 41 erstklassige Schnittfestigkeit sowie ein langes Reifenleben. Neben langen Betriebsstunden ohne Maschinenstillstand bietet der Reifen außergewöhnlichen Komfort.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Knickgelenkter Muldenkipper • Planierer • Radlader  
• flache Dumper

| SIZE                        | Version                      | USACode  | TRA Code | Star R | LI/SS        | RIM REC    | RIM ALT              | OW   | OD   | SLR  | RC    | Type | TMPH |
|-----------------------------|------------------------------|----------|----------|--------|--------------|------------|----------------------|------|------|------|-------|------|------|
| 23.5 R 25                   | CUT RESISTANT COMPOUND       | 94053353 | E4/L4    | **/*   | 185 B/195 A2 | 19.50/2.5  |                      | 24.2 | 63.4 | 28.5 | 188.6 | TL   | 110  |
| 26.5 R 25                   | CUT RESISTANT COMPOUND       | 94041206 | E4/L4    | **/*   | 193 B/202 A2 | 22.00/3.0  |                      | 26.7 | 68.6 | 30.5 | 202.8 | TL   | 127  |
| 26.5 R 25                   | CUT RESISTANT COMPOUND (UMS) | 94056583 | E4       | ****   |              | 22.00/3.0  |                      | 26.7 | 68.6 | 30.5 | 202.8 | TL   | 0    |
| 26.5 R 25                   | STANDARD COMPOUND            | 94041527 | E4       | **     | 193 B        | 22.00/3.0  |                      | 26.7 | 68.6 | 30.5 | 202.8 | TL   | 161  |
| 29.5 R 25                   | CUT RESISTANT COMPOUND       | 94058013 | E4       | **     | 200 B        | 25.00/3.5  |                      | 30   | 73.3 | 32.7 | 216.9 | TL   | 154  |
| 29.5 R 25                   | CUT RESISTANT COMPOUND       | 94070367 | L4       | ***    | 221 A2       | 25.00/3.5  |                      | 30   | 73.3 | 32.7 | 216.9 | TL   | 0    |
| 29.5 R 25                   | CUT RESISTANT COMPOUND       | 94039852 | E4/L4    | **/*   | 200 B/208 A2 | 25.00/3.5  |                      | 30   | 73.3 | 32.7 | 216.9 | TL   | 154  |
| 29.5 R 25                   | CUT RESISTANT COMPOUND (UMS) | 94051052 | E4       | ****   |              | 25.00/3.5  |                      | 30   | 73.3 | 32.7 | 216.9 | TL   | 0    |
| 29.5 R 25                   | STANDARD COMPOUND            | 94041169 | E4       | **     | 200 B        | 25.00/3.5  |                      | 30   | 73.3 | 32.7 | 216.9 | TL   | 195  |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND       | 94059911 | E4/L4    | **/*   | 203 B/214 A2 | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 34.6 | 73.4 | 33   | 223.6 | TL   | 164  |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND       | 94059928 | E4       | **     | 203 B        | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 34.6 | 73.4 | 33   | 223.6 | TL   | 164  |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND       | 94059935 | L4       | *      | 214 A2       | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 34.6 | 73.4 | 33   | 223.6 | TL   | 0    |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND       | 94064359 | L4       | **     | 221 A2       | 27.00/3.5  | 27.00/3.0; 28.00/3.5 | 34.6 | 73.4 | 33   | 223.6 | TL   | 0    |
| 35/65 R 33                  | CUT RESISTANT COMPOUND (UMS) | 94069415 | E4       | ****   |              | 28.00/3.5  | --                   | 35.3 | 81.2 | 36.5 | 247.4 | TL   | 0    |

Printed on 19.05.2024 00:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..