

EARTHMAX SR 44 - Technische Daten



Description

EARTHMAX SR 44 ist ein **All Steel** Radialreifen, der sich für zahlreiche Anwendungen eignet, u.a. im Bergbau, Transport und Forstbetrieb. Das widerstandsfähige E-4 Reifenprofil sichert sowohl ausgezeichnete Traktion als auch Bedienerkomfort. EARTHMAX SR 44 (E-4) ist in der Lage, Ihre Produktivität zu optimieren, gleich in welchem Gebiet er zum Einsatz kommt.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Kipper

Version	STANDARD
Type	TT
Tyre Size	7.50 R 16
LI/SS	122/118 G

Dimensions International Standard

Overall Width (mm)	226
Overall Diameter (mm)	820
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2450
Rim Rec	6
Rim Alt	5.5, 6.5

Load capacity (Kg)

km/h / bar	7.25
90 LS	1500
90 LD	1320

Printed on 18.05.2024 23:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..