

EARTHMAX SR 49 M - Datenblatt



Description

EARTHMAX SR 49 M ist ein All Steel Radialreifen mit einem speziellen, nicht-richtungsgebundenem Muster, der speziell für Fahrlader (LHD), flache Dumper (LPDT) sowie Radlader und Planierer entwickelt wurde, die unter schweren Bedingungen in felsiger Umgebung vor allem im Untertagebau eingesetzt werden. EARTHMAX SR 49 M ist ideal für Arbeiten, die hervorragende Traktion und Stabilität erfordern. Das tiefe L-4 Laufflächenprofil und die speziell formulierte Gummimischung UMS (underground mine service) verleihen eine größere Verschleißfestigkeit neben ausgezeichneter Widerstandsfähigkeit gegenüber Schnitten an Felsen und Stichen.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Planierer • Fahrlader LHD • Radlader • flache Dumper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
26.5 R 25	CUT RESISTANT COMPOUND	L4	**	209 A2	22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	193 B/202 A2	22.00/3.0		708	1782	801	5297	TL	165
26.5 R 25	CUT RESISTANT COMPOUND	L4	*	202 A2	22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	****/***		22.00/3.0		708	1782	801	5297	TL	
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		22.00/3.0		708	1782	801	5297	TL	
29.5 R 25	CUT RESISTANT COMPOUND	L4	*	208 A2	25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND	L4	**	216 A2	25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	200 B/208 A2	25.00/3.5		780	1905	844	5600	TL	220
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	****/***		25.00/3.5		780	1905	844	5600	TL	
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		25.00/3.5		780	1905	844	5600	TL	
29.5 R 29	CUT RESISTANT COMPOUND	L4	***	223 A2	25.00/3.5	24.00/3.5,26.00/3.5	786	2006	906	6320	TL	
29.5 R 29	CUT RESISTANT COMPOUND (UMS)	E4	****		25.00/3.5	24.00/3.5, 26.00/3.5	786	2006	906	6320	TL	

Printed on 18.05.2024 18:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..