

AGRIMAX ELOS - Ficha técnica



Description

AGRIMAX ELOS ha sido proyectado para ofrecer la máxima tracción en condiciones de uso particularmente problemáticas en terrenos mojados - como por ejemplo los arrozales - y pantanosos. El dibujo de la banda de rodadura ha sido estudiado para garantizar óptimas cualidades de auto-limpieza, esenciales en los trabajos realizados en terrenos fangosos y durante los desplazamientos. Para optimizar la productividad de la empresa agrícola, en el dibujo del neumático AGRIMAX ELOS se han integrado unas protecciones en los flancos para asegurar la máxima protección ante posibles daños.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

| SIZE | Version | USACode | TRA Code | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|--------------------------------|----------|----------|----------|--------------|---------|---|------|------|------|-------|------|------------------|
| 420/85 R 28 (16.9 R 28) | STANDARD | 94040810 | R2 | 139 A8/B | W 15 L | W 13 ; W 14 L | 17.2 | 57.8 | 26.2 | 171.2 | TL | E4-106R-000768 |
| 480/70 R 34 | STANDARD | 94070299 | R2 | 155 A8/155 B | W 15 L | W 16 L ; W 14 L | 19.7 | 63.2 | 28.9 | 191.7 | TL | E11-106R-007532 |
| 340/85 R 38 (13.6 R 38) | STANDARD | 94040452 | R2 | 133 A8/B | W 12 | W 11 | 13.9 | 63.1 | 28.9 | 188 | TL | E4-106R-001477 |
| 380/85 R 38 (14.9 R 38) | STANDARD | 94036134 | R2 | 139 A8/B | W 12 | W 11 ; W 13 | 15 | 65.4 | 30.4 | 196.6 | TL | E4-106R-000779 |
| 420/85 R 38 (16.9 R 38) | STANDARD | 94034512 | R2 | 144 A8/B | W 15 L | W 13 ; W 14 L | 17.2 | 68.3 | 30.9 | 202.2 | TL | E4-106R-000780 |
| 480/80 R 38 (18.4 R 38) | STANDARD | 94053766 | R2 | 149 A8/B | W 16 L | W 15 L ; DW 16 L | 19.3 | 71 | 32.3 | 210.9 | TL | E11-106R-002991 |
| 710/70 R 38 | STANDARD | 94058617 | R2 | 178 A8/B | DW 23 B | DW 25 B | 28.2 | 79.5 | 36 | 240.3 | TL | E11-106R-004896 |
| 480/80 R 42 (18.4 R 42) | STANDARD | 94040827 | R2 | 151 A8/B | DW 16 L | DD 16 L ; W 16 L | 19.3 | 74.4 | 33.7 | 221.6 | TL | E4-106R-001481 |
| 520/85 R 42 (20.8 R 42) | STANDARD | 94040834 | R2 | 157 A8/B | DW 16 L | DD 18 L ; DW 18 L | 20.3 | 78.3 | 35.6 | 230.9 | TL | E4-106R-000793 |
| 520/85 R 42 (20.8 R 42) | STANDARD | 94075850 | R2 | 167A8/B | DW 16 L | DD 18 L ; DW 18 L | 20.3 | 78.3 | 36.2 | 240 | TL | E11-106R-0010146 |
| 520/85 R 46 | STANDARD | 94070503 | R2 | 169 A8/169 B | DW 16 L | DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L | 20.9 | 81.7 | 37.7 | 247.8 | TL | E11-106R-007935 |

Printed on 18/05/2024 23:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..