

AGRIMAX FORTIS - Especificaciones técnicas



Description

AGRIMAX FORTIS es vuestro compañero más fiable para todas las operaciones de preparación y tratamiento del terreno y de transporte. Diseñado para equipar los tractores más potentes de última generación, AGRIMAX FORTIS permite transportar cargas muy elevadas con velocidades hasta 65 km/h. Asegura una tracción excelente además de una duración superior y un gran confort para una experiencia perfecta de conducción. El neumático ha sido desarrollado con una carcasa reforzada de nylon que mejora la productividad en los campos y preserva el suelo gracias a una menor compactación.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador

Version	SPECIAL
Type	TL
Tyre Size	600/70 R 34
LI/SS	160 D/163 A8

Dimensions US Standard

Usa code	94050116
Section Width (inch)	23.3
Overall Diameter (inch)	67.1
Static Loaded Radius (inch)	30
Rolling Circumference (inch)	201.1
Rim Rec	DW 18 L
Rim Alt	DW 20 B ; W 18 L
ECE	E4-106R-001401
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4760	5560	6250	6940	7640	8230	9130	9920
30	5000	5840	6570	7300	8020	8650	9590	10420
25	5160	6020	6780	7530	8280	8930	9890	10750
20	5480	6390	7200	7990	8780	9480	10500	11410
5 LT	6380	7450	8380	9310	10240	11030	12230	13290
5 HT	5480	6390	7200	7990	8780	9480	10500	11410

Printed on 18/05/2024 22:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..