

AGRIMAX SPARGO - Especificaciones técnicas



Description

AGRIMAX SPARGO es el neumático BKT específico para aplicaciones de cultivos en hileras, proyectado para reforzar la productividad del terreno y conservarlo a largo plazo. Este neumático posee óptimas cualidades de auto-limpieza y una capacidad de carga superior con el inflado estándar. AGRIMAX Spargo garantiza una óptima tracción, combinada con una fuerte estabilidad tanto en el campo como durante los desplazamientos por carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 42
LI/SS	163 D

Dimensions US Standard

Usa code	94070978
Section Width (inch)	12.7
Overall Diameter (inch)	64.6
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	196.7
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-007813
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	4870	5380	5880	6180	6480	6670	6870	7210	7570	7860	8160	8420	8660	8910	9150	9550	9950
From 40 to 25	5160	5810	6350	6670	6990	7210	7420	7800	8170	8500	8820	9090	9360	9630	9890	10320	10750
20	5270	5940	6490	6810	7140	7360	7580	7960	8350	8680	9000	9270	9550	9830	10100	10540	10970
12	5370	6050	6610	6940	7280	7500	7720	8120	8500	8850	9180	9450	9740	10010	10290	10740	11180
5	5690	6400	6990	7350	7700	7930	8170	8580	9000	9350	9700	10000	10300	10600	10900	11370	11830

Printed on 18/05/2024 22:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..