

AGRIMAX SPARGO - Especificaciones técnicas



Description

AGRIMAX SPARGO es el neumático BKT específico para aplicaciones de cultivos en hileras, proyectado para reforzar la productividad del terreno y conservarlo a largo plazo. Este neumático posee óptimas cualidades de auto-limpieza y una capacidad de carga superior con el inflado estándar. AGRIMAX Spargo garantiza una óptima tracción, combinada con una fuerte estabilidad tanto en el campo como durante los desplazamientos por carretera.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador

Version	STEEL BELTED
Type	TL
Tyre Size	VF750/60R46
LI/SS	189 D

Dimensions International Standard

Section Width (mm)	755
Overall Diameter (mm)	2086
Static Loaded Radius (mm)	940
Rolling Circumference (mm)	6337
SRI (mm)	975
Rim Rec	DW27B
ECE	E11-106R-009075
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	5525	6100	6765	7145	7525	7815	8100	8480	8860	9195	9525
From 65 to 40	5975	6595	7315	7725	8140	8450	8755	9170	9580	9940	10300
30	6100	6730	7465	7885	8305	8620	8935	9355	9775	10145	10510
20	6215	6860	7610	8040	8465	8790	9110	9540	9965	10340	10715
10	6575	7255	8045	8500	8955	9295	9635	10085	10540	10935	11330

Printed on 19/05/2024 0:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..