

AGRIMAX SPARGO - Ficha técnica



Description

AGRIMAX SPARGO es el neumático BKT específico para aplicaciones de cultivos en hileras, proyectado para reforzar la productividad del terreno y conservarlo a largo plazo. Este neumático posee óptimas cualidades de auto-limpieza y una capacidad de carga superior con el inflado estándar. AGRIMAX Spargo garantiza una óptima tracción, combinada con una fuerte estabilidad tanto en el campo como durante los desplazamientos por carretera.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
VF 380/85 R 34	STANDARD	R1	160 D	W 13 A	W 12	380	1500	678	4514	725	TL	E11-106R-009071
VF 380/85 R 38	STANDARD	R1	161 D	W 13 A	W 12	380	1602	730	4830	775	TL	E4-106R-001482
VF 320/90 R 42	STANDARD	R1	163 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1642	764	4995	775	TL	E11-106R-007813
VF 480/80 R 42	STANDARD	R1	176 D	DW 16 L	DW 15 L	479	1835	838	5572	875	TL	E11-106R-009072
VF 320/90 R 46	STANDARD	R1	165 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1743	810	5316	825	TL	E11-106R-0010077
VF 380/90 R 46	STANDARD	R1	173 D	DW 13 B	W 13 A ; DW 12	390	1852	846	5611	875	TL	E4-106R-000796
VF 380/90 R 46	STANDARD	R1	175 D	DW 13 B	W 13 A ; DW 12	390	1852	848	5582	875	TL	E11-106R-007527
VF 480/80 R 46	STANDARD	R1	177 D	DW 16 L	DW 15 L	479	1936	892	5907	925	TL	E11-106R-004756
VF750/60R46	STEEL BELTED	R1	189 D	DW27B		755	2086	940	6337	975	TL	E11-106R-009075
VF 320/90 R 50	STANDARD	R1	169 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1846	865	5650	875	TL	E11-106R-007204
VF 380/105 R 50	STANDARD	R1	179 D	W 13 A	W 12 ; DW 12 ; DW 13 ; DW 13 L	400	2050	934	6211	975	TL	E4-106R-002397
VF 380/90 R 50	STANDARD	R1	175 D	W13 B	W12 B	390	1950	893	5950	925	TL	E11-106R-006400
VF 420/95 R 50	STANDARD	R1	177 D	DW 14	DW 13 ; W 13 ; W 14	419	2068	943	6210	975	TL	E4-106R-002651
VF 480/80 R 50	STANDARD	R1	179 D	DW 16 L	DW 15 L	479	2038	947	6224	975	TL	E11-106R-004757
VF 480/95 R 50	STANDARD	R1	181 D	DW 16 L	DW 15 L	479	2182	991	6606	1025	TL	E11-106R-0010083
VF 320/90 R 54 CFO	STANDARD	R1	168 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1948	910	5946	925	TL	E11-106R-009070
VF 380/105 R 54	STANDARD	R1	180 D	W 13 A	W 12 ; DW 12 ; DW 13 ; DW 13 L	400	2140	984	6503	1050	TL	E11-106R-0010148
VF 380/90 R 54	STANDARD	R1	176 D	W13	DW 13 ; DW 12 ; W 12	383	2056	948	6232	975	TL	E11-106R-0010081

Printed on 18/05/2024 21:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..