

## AGRIMAX TERIS - Especificaciones técnicas



### Description

Las actuales cosechadoras de elevada potencia requieren neumáticos capaces de soportar máquinas y cargas pesadas sin dañar los cultivos. BKT se compromete a ofrecer las soluciones de neumáticos radiales a la vanguardia para aumentar el rendimiento de su cosecha. AGRIMAX TERIS es el compañero ideal para sus operaciones combinadas. Excelente tracción y elevada capacidad de carga son las dos características fundamentales que se traducen en el mejor rendimiento para todas las operaciones de la cosecha. La protección del flanco y el hombro redondeado incrementan la resistencia – alargando el ciclo de vida del producto – incluso en condiciones adversas aunque hay los rastros en el campo.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cosechadora de algodón • Cosechadora

Version	STANDARD
Type	TL
Tyre Size	800/65 R 32 CHO (30.5L R 32)
LI/SS	178 A8/175 B

## Dimensions US Standard

Usa code	94031412
Section Width (inch)	32.2
Overall Diameter (inch)	73
Static Loaded Radius (inch)	33
Rolling Circumference (inch)	218.5
Rim Rec	DW 27 B
Rim Alt	DW 25 B ; DH 27 B
ECE	E4-106R-001430

## Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	7000	8070	9890	10800	12030	12930	14150	15210
25	7610	8760	10750	11740	13060	14050	15380	16530
20	8150	9380	11510	12570	13980	15050	16460	17690
10 Cyc	12550	14460	17740	19380	21560	23190	25370	27280
5 Cyc	13690	15770	19340	21130	23510	25300	27680	29760

Printed on 04/05/2024 18:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..