

AGRIMAX TERIS - Especificaciones técnicas



Description

Las actuales cosechadoras de elevada potencia requieren neumáticos capaces de soportar máquinas y cargas pesadas sin dañar los cultivos. BKT se compromete a ofrecer las soluciones de neumáticos radiales a la vanguardia para aumentar el rendimiento de su cosecha. AGRIMAX TERIS es el compañero ideal para sus operaciones combinadas. Excelente tracción y elevada capacidad de carga son las dos características fundamentales que se traducen en el mejor rendimiento para todas las operaciones de la cosecha. La protección del flanco y el hombro redondeado incrementan la resistencia – alargando el ciclo de vida del producto – incluso en condiciones adversas aunque hay los rastros en el campo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora de algodón • Cosechadora

Version	STANDARD
Type	TL
Tyre Size	IF 710/75 R 32 CFO
LI/SS	183 A8/B

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	1879
Static Loaded Radius (mm)	851
Rolling Circumference (mm)	5653
SRI (mm)	875
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-005025

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3415	4025	4640	5775	6300	6915	7440	8140	8750
40	3415	4025	4640	5775	6300	6915	7440	8140	8750
30	3655	4310	4965	6185	6745	7400	7965	8710	9365
15 Cyc*	5295	6240	7190	8955	9770	10720	11535	12620	13565
10 Cyc*	6145	7245	8350	10395	11340	12445	13390	14650	15750

* - * For 15 & 10 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 04/05/2024 18:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..