

## AGRIMAX V-FLECTO - Especificaciones técnicas



### Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafiante en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la tecnología exclusiva VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 540/65 R 30 NRO
LI/SS	158 D

## Dimensions US Standard

Usa code	94062133
Section Width (inch)	21.6
Overall Diameter (inch)	57.6
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	171.3
Rim Rec	DW 20 B
Rim Alt	DW 18 L
Narrow Rim option	DW 16 L
ECE	E11-106R-005711
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	4340	5020	5700	6470	7070	7670	8520
from 40 to 25	4770	5520	6270	7120	7770	8430	9370
20	4860	5630	6390	7250	7930	8600	9560
12	4960	5740	6510	7400	8080	8760	9740
5	5250	6070	6890	7830	8540	9270	10310
*Upto 5 Cyc with front loader	6680	7730	8770	9960	10880	11810	13120
5 HT	4860	5630	6390	7250	7930	8600	9560

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 04/05/2024 16:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..