

AGRIMAX V-FLECTO - Especificaciones técnicas



Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafiante en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la tecnología exclusiva VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 540/65 R 38 NRO
LI/SS	162 D

Dimensions US Standard

Usa code	94059119
Section Width (inch)	21.6
Overall Diameter (inch)	66
Static Loaded Radius (inch)	29.9
Rolling Circumference (inch)	196.1
Rim Rec	DW 20 B
Rim Alt	DW 18 L
Narrow Rim option	DW 16 L
ECE	E11-106R-005020
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	4850	5610	6370	7240	7900	8580	9520
from 40 to 25	5330	6170	7010	7960	8690	9420	10470
20	5430	6290	7140	8110	8850	9610	10680
12	5540	6420	7290	8270	9030	9800	10890
5	5860	6790	7700	8750	9550	10360	11520
*Upto 5 Cyc with front loader	7460	8640	9810	11130	12160	13190	14660
5 HT	5430	6290	7140	8110	8850	9610	10680

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 04/05/2024 19:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..