

AGRIMAX V-FLECTO - Especificaciones técnicas



Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafiante en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la tecnología exclusiva VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 580/85 R 42 CFO
LI/SS	183 D

Dimensions International Standard

Section Width (mm)	606
Overall Diameter (mm)	2058
Static Loaded Radius (mm)	923
Rolling Circumference (mm)	6166
SRI (mm)	975
Rim Rec	DW20B
Rim Alt	DW18B ; MW20B
ECE	E11-106R-006444
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
70	3425	3980	4540	5095	5655	6210	6850	7245	7960
From 65 to 40	3765	4375	4990	5600	6215	6825	7525	7965	8750
30	3840	4465	5090	5715	6340	6965	7680	8125	8925
20	3915	4550	5190	5825	6465	7100	7830	8285	9100
10	4140	4815	5490	6160	6835	7510	8280	8760	9625
Upto 30 Cyc	4270	4965	5665	6360	7055	7750	8540	9040	9930
Upto 15 Cyc	5100	5930	6760	7590	8420	9250	10200	10790	11855
Upto 10 Cyc	5590	6495	7405	8315	9225	10135	11175	11825	12990
10 HT	3840	4465	5090	5715	6340	6965	7680	8125	8925

Printed on 04/05/2024 20:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..