

AT 621 - Especificaciones técnicas



Description

AT 621 es idóneo para las ternas y las palas compactas que se utilizan en todas las operaciones de excavación y carga en el ámbito agrícola. La banda de rodadura del AT 621 es extra profunda, asegurando una excepcional resistencia a los cortes y los desgarros así como una mayor durabilidad. Además, este neumático asegura optimas propiedades de auto-limpieza. AT 621 está disponible en varias versiones con el fin de responder a las diferentes exigencias de los usuarios.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora compacta • Cargadora retroexcavadora

Industrial: Cargadora retroexcavadora • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS	127 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	267
Overall Diameter (mm)	780
Static Loaded Radius (mm)	373
Rolling Circumference (mm)	2385
Rim Rec	9.0
ECE	E11-106R-007466

Load capacity (Kg)

km/h / bar	5.25
30	1750

Printed on 04/05/2024 19:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..