

AT 621 - Especificaciones técnicas



Description

AT 621 es idóneo para las ternas y las palas compactas que se utilizan en todas las operaciones de excavación y carga en el ámbito agrícola. La banda de rodadura del AT 621 es extra profunda, asegurando una excepcional resistencia a los cortes y los desgarros así como una mayor durabilidad. Además, este neumático asegura optimas propiedades de auto-limpieza. AT 621 está disponible en varias versiones con el fin de responder a las diferentes exigencias de los usuarios.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora compacta • Cargadora retroexcavadora

Industrial: Cargadora retroexcavadora • Pala cargadora

Version	INDUSTRIAL HD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8

Dimensions US Standard

Usa code	94032730
Ply Rating	16
Section Width (inch)	12.1
Overall Diameter (inch)	38.9
Static Loaded Radius (inch)	17.1
Rolling Circumference (inch)	114.8
Rim Rec	W 9
Rim Alt	11.0
ECE	E11-106R-005365
TRA Code	R4

Load capacity (lbs)

mph / psi	71
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940
5 DW	6720
15 DW	5720
20 DW	5380
25 DW	4810

Printed on 04/05/2024 18:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..