

## BK-LOADER 53 - Especificaciones técnicas



### Description

BK-LOADER 53 es un neumático con cinturones de aramida desarrollado para las palas cargadoras utilizadas en las aplicaciones industriales. El dibujo especial de la banda de rodadura garantiza una óptima estabilidad lateral, además, gracias a la banda de rodadura extra profunda también se obtiene una extraordinaria resistencia al desgaste, a los cortes y a los pinchazos. BK-LOADER 53 se caracteriza por sus excepcionales propiedades de auto-limpieza, así como por su excelente agarre y tracción sobre las superficies mojadas y secas. Por último, este neumático es particularmente adecuado para las operaciones de reciclaje.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Pala cargadora

Version	ARAMID BELTED
Type	TL
Tyre Size	365/70 R 18
LI/SS	146A2/142A4

## Dimensions International Standard

Section Width (mm)	360
Overall Diameter (mm)	990
Static Loaded Radius (mm)	458
Rolling Circumference (mm)	3017
Rim Rec	11

## Load capacity (Kg)

km/h / bar	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
20 TRANSPORT	930	1195	1405	1620	1855	2045	2255	2440	2650
10 LOADING	1050	1350	1590	1830	2100	2310	2550	2760	3000
STATIC	1670	2150	2530	2910	3340	3675	4055	4390	4770

Printed on 05/05/2024 8:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..