

EARTHMAX SR 313 - Ficha técnica



Description

EARTHMAX SR 313 es un neumático radial All Steel diseñado específicamente para volquetes articulados y las cargadoras que operan en condiciones rocosas duras. Su compuesto resistente a los cortes y el diseño especial de la banda de rodadura protegen contra cortes y daños, además de ofrecer propiedades de autolimpieza. Su diseño de hombro cuadrado maximiza el contacto con el suelo para lograr una excelente maniobrabilidad. La estructura radial All Steel con correas de acero de varias capas garantiza una mayor durabilidad. EARTHMAX SR 313 es el neumático ideal para las operaciones de arrastre y carga y transporte.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Volquete articulado • Pala cargadora

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
15.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	160 B/169 A2	12.00/1.3		394	1265	566	3822	TL	135

Printed on 05/05/2024 5:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..