

## EARTHMAX SR 468 - Especificaciones técnicas



### Description

EARTHMAX SR 468 es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos. Su exclusivo diseño de la banda de rodadura con compuestos especiales la hace perfecta para condiciones mineras duras y rocosas. Sus tacos con ranuras circunferenciales y bloques entrelazados garantizan una disipación eficaz del calor. Además, el robusto hombro cuadrado ayuda a expulsar las piedras sueltas para proteger el neumático contra daños. EARTHMAX SR 468 se ha desarrollado con la tecnología de vanguardia de BKT para soportar cargas pesadas, ofrecer una mayor vida útil y proporcionar resistencia a los cortes y pinchazos de las rocas.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dúmper rígido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	37.00 R 57
LI/SS	245 B

## Dimensions US Standard

Usa code	94069361
TMPH	582
Overall Width (inch)	40.6
Overall Diameter (inch)	134.8
Static Loaded Radius (inch)	59.8
Rolling Circumference (inch)	406.1
Rim Rec	27.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	80	83	87	91	94	98	102
30	96500	99000	102000	104500	107500	110000	113500

Printed on 05/05/2024 10:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..