

EARTHMAX SR 46 - Especificaciones técnicas



Description

Earthmax SR 46 para dumpers rígidos es la respuesta innovadora para los ambientes rocosos, abrasivos y hostiles de las minas. Este neumático ha sido particularmente proyectado para el transporte de cargas pesadas y ofrece una excepcional resistencia a los cortes y las laceraciones, así como un ciclo de vida más largo del producto. La carcasa y los cinturones **All Steel** aseguran una protección extraordinaria contra los golpes, las solicitaciones y los pinchazos, maximizando las horas operativas e incrementando la productividad. Earthmax SR 46 se caracteriza por un especial diseño de la banda de rodadura, provisto de tacos en bloques y ranura a lo largo de la circunferencia. Esto significa óptimas prestaciones en las curvas, con el mínimo daño a la parte exterior de la banda de rodadura.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Dúmpfer rígido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	30.00 R 51
LI/SS	230 B

Dimensions US Standard

Usa code	94074754
TMPH	418
Overall Width (inch)	32.9
Overall Diameter (inch)	114
Static Loaded Radius (inch)	51.2
Rolling Circumference (inch)	346.5
Rim Rec	22.00/4.5
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	56800	58400	61500	64000	66000	68000	69500	71500	74000

Printed on 04/05/2024 20:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..