

## EARTHMAX SR 484 - Ficha técnica



### Description

EARTHMAX SR 484 es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos para el transporte en aplicaciones de minería de superficie. Presenta un exclusivo diseño de banda de rodadura E-3 con un compuesto especial que garantiza una excelente protección en condiciones duras y rocosas, junto con una mayor tracción y unas propiedades de autolimpieza excelentes. Su construcción All Steel con cinturones de acero multicapa permite una protección superior contra golpes, fatiga y perforación de rocas, lo que mejora el tiempo de funcionamiento y aumenta la productividad. EARTHMAX SR 484 cuenta con diseño de hombro cuadrado, que maximiza el contacto con el suelo para lograr una maniobrabilidad y una estabilidad excelentes. Este neumático BKT está especialmente diseñado para velocidades más altas y trayectos largos.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dúmpers rígidos

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
27.00 R 49	CUT RESISTANT COMPOUND	94067817	E3	**	223 B	19.50/4.0	--	28.9	104.2	47	317.1	TL	360
27.00 R 49	HEAT RESISTANT COMPOUND	94067824	E3	**	223 B	19.50/4.0	--	28.9	104.2	47	317.1	TL	486
27.00 R 49	STANDARD COMPOUND	94067831	E3	**	223 B	19.50/4.0	--	28.9	104.2	47	317.1	TL	418

Printed on 04/05/2024 21:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..