

EARTHMAX SR 49 M - Especificaciones técnicas



Description

EARTHMAX SR 49 M es un neumático radial All Steel con un dibujo no direccional particularmente proyectado para cargadoras LHD, volquetes de perfil bajo, palas cargadoras y buldóceros de que operan en las severas condiciones de los ambientes rocosos, principalmente en las minas subterráneas. EARTHMAX SR 49 M es ideal para las operaciones más duras que requieren una excepcional tracción y estabilidad excelente. La profundidad L-4 de la banda de rodadura y la fórmula especial UMS (underground mine service) de la mezcla, aseguran una mayor resistencia al desgaste, así como una excelente resistencia contra los cortes y los pinchazos causados por las rocas.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora • Volquete de perfil bajo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

Dimensions US Standard

Usa code	94058426
TMPH	151
Overall Width (inch)	30.7
Overall Diameter (inch)	75
Static Loaded Radius (inch)	33.2
Rolling Circumference (inch)	220.5
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E4/L4

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	--

Printed on 04/05/2024 20:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..