

## EARTHMAX SR 55 - Ficha técnica



### Description

EARTHMAX SR 55 (L-55) es un neumático radial All Steel especialmente proyectado para las palas cargadoras, los buldóceres y las cargadoras que operan en condiciones muy difíciles, como en las canteras, las minas y en los depósitos de chatarra. Gracias al dibujo de la banda de rodadura extra profundo y liso, EARTHMAX SR 55 puede alcanzar elevados niveles de productividad con menores tiempos de parada de la máquina. Los operadores de las máquinas apreciarán también estabilidad y tracción extraordinarias.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora

| SIZE       | Version                | TRA Code | Star R | LI/SS  | RIM REC   | RIM ALT              | OW  | OD   | SLR | RC   | Type |
|------------|------------------------|----------|--------|--------|-----------|----------------------|-----|------|-----|------|------|
| 12.00 R 24 | CUT RESISTANT COMPOUND | L5S      | **     | 175 A2 | 8.50/1.3  | 8.0,9.0              | 305 | 1274 | 572 | 3787 | TT   |
| 12.00 R 24 | CUT RESISTANT COMPOUND | L5S      | **     | 175 A2 | 8.50/1.3  | 8.0,9.0              | 305 | 1274 | 572 | 3787 | TL   |
| 17.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 182 A2 | 14.00/1.5 |                      | 453 | 1399 | 630 | 4211 | TL   |
| 17.5 R 25  | CUT RESISTANT COMPOUND | L5S      | ***    | 188 A2 | 14.00/1.5 |                      | 453 | 1399 | 630 | 4211 | TL   |
| 18.00 R 25 | CUT RESISTANT COMPOUND | L5S      | **     | 204 A2 | 13.00/2.5 |                      | 513 | 1667 | 733 | 4852 | TL   |
| 20.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 193 A2 | 17.00/2.0 |                      | 535 | 1543 | 700 | 4644 | TL   |
| 26.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 209 A2 | 22.00/3.0 |                      | 690 | 1786 | 810 | 5375 | TL   |
| 26.5 R 25  | CUT RESISTANT COMPOUND | L5S      | ***    | 214 A2 | 22.00/3.0 |                      | 690 | 1786 | 810 | 5375 | TL   |
| 29.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 216 A2 | 25.00/3.5 |                      | 777 | 1912 | 860 | 5755 | TL   |
| 29.5 R 29  | CUT RESISTANT COMPOUND | L5S      | **     | 218 A2 | 25.00/3.5 | 24.00/3.5, 26.00/3.5 | 775 | 2009 | 911 | 6047 | TL   |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L5S      | ***    | 229 A2 | 28.00/3.5 | --                   | 900 | 2065 | 915 | 6175 | TL   |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L5S      | **     | 224 A2 | 28.00/3.5 | --                   | 900 | 2065 | 915 | 6175 | TL   |

Printed on 05/05/2024 5:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..