

FL 630 SUPER - Especificaciones técnicas



Description

FL 630 SUPER es un neumático de flotación particularmente idóneo para utilizarlo con remolques, auto cisternas y pulverizadores. Su estructura resistente proporciona una excelente tracción y un agarre perfecto incluso en las curvas y durante las maniobras. El particular dibujo de la banda de rodadura garantiza una perfecta adherencia en cualquier tipo de terreno, así como avanzadas propiedades de auto-limpieza. FL 630 SUPER permite velocidades hasta 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 580/65 R 22.5 |
| LI/SS | 166 D |

Dimensions US Standard

| | |
|------------------------------|--------------------------------|
| Usa code | 94045037 |
| Section Width (inch) | 22.7 |
| Overall Diameter (inch) | 52.2 |
| Static Loaded Radius (inch) | 23.4 |
| Rolling Circumference (inch) | 159.8 |
| Rim Rec | AG 18.00 |
| Rim Alt | AG 16.00 ; AG 17.00 ; AG 20.00 |
| ECE | E4-106R-001416 |

Load capacity (lbs)

| mph / psi | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 3440 | 3980 | 4520 | 5380 | 6350 | 7260 | 8070 | 9030 | 9890 | 10750 |
| 40 | 3750 | 4330 | 4920 | 5840 | 6900 | 7890 | 8760 | 9820 | 10760 | 11680 |
| 30 | 4530 | 5240 | 5940 | 7080 | 8340 | 9560 | 10610 | 11880 | 13020 | 14140 |
| 25 | 5090 | 5890 | 6680 | 7950 | 9380 | 10740 | 11930 | 13360 | 14630 | 15890 |
| 15 | 5910 | 6830 | 7760 | 9240 | 10900 | 12470 | 13860 | 15510 | 16990 | 18460 |
| 5 | 6730 | 7790 | 8840 | 10520 | 12410 | 14200 | 15770 | 17670 | 19360 | 21030 |

Printed on 18/05/2024 21:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..