

FL 635 - Especificaciones técnicas



Description

FL 635 es un neumático radial de flotación idóneo para utilizarlo por carretera y en el campo. El particular dibujo de bloques de la banda de rodadura ha sido desarrollado para aplicaciones de prensas para empacar la paja. Gracias a la huella que proporciona una óptima distribución de la presión en el terreno, el neumático FL 635 reduce netamente la compactación del suelo, preservando el valor de los cultivos. El neumático asegura optimas propiedades de auto-limpieza, durabilidad y tracción además de excelentes prestaciones de velocidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Empacadora de heno

Version	STANDARD
Type	TL
Tyre Size	500/45 R 22.5
LI/SS	136 D

Dimensions International Standard

Section Width (mm)	490
Overall Diameter (mm)	1022
Static Loaded Radius (mm)	461
Rolling Circumference (mm)	3086
SRI (mm)	500
Rim Rec	AG 16.00
ECE	E11-106R-0010082

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8
70	1125	1370	1555	1800	2040
65	1235	1505	1705	1975	2240
50	1495	1820	2065	2390	2715
40	1680	2045	2320	2685	3050
30	1865	2270	2575	2980	3385
25	1950	2375	2695	3120	3540
10	2220	2705	3070	3555	4035

Printed on 18/05/2024 23:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..