

FL 635 - Ficha técnica



Description

FL 635 es un neumático radial de flotación idóneo para utilizarlo por carretera y en el campo. El particular dibujo de bloques de la banda de rodadura ha sido desarrollado para aplicaciones de prensas para empacar la paja. Gracias a la huella que proporciona una óptima distribución de la presión en el terreno, el neumático FL 635 reduce netamente la compactación del suelo, preservando el valor de los cultivos. El neumático asegura optimas propiedades de auto-limpieza, durabilidad y tracción además de excelentes prestaciones de velocidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Empacadora de heno

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/45 R 22.5	STANDARD	94075607	136 D	AG 16.00		19.3	40.2	18.1	121.5	TL	E11-106R-0010082
620/40 R 22.5	STANDARD	94048038	154 D	AG 20.00		24.6	42	18.5	127.9	TL	E4-106R-002399
650/55 R 22.5	STANDARD	94043521	167 D	AG 20.00		25.4	50.7	22.4	153.6	TL	E4-106R-000803
710/40 R 22.5	STANDARD	94053285	161 D	AG 24.00		28.6	44.9	20.1	136.5	TL	E11-106R-003014
750/45 R 22.5	STANDARD	94048786	168 D	AG 24.00		29.7	49.1	21.9	150	TL	E4-106R-002653

Printed on 18/05/2024 22:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..