

MULTIMAX MP 522 - Especificaciones técnicas



Description

MULTIMAX MP 522 es un neumático polivalente desarrollado por BKT para aplicaciones en el sector agro-industrial. Es idóneo para todas las operaciones de levantamiento y carga realizadas con elevadores telescópicos y palas compactas. Los puntos de fuerza son su excelente estabilidad y tracción, así como la excepcional resistencia a las perforaciones. MULTIMAX MP 522 ofrece una resistencia extraordinaria contra los cortes y los desgarres gracias a su mezcla especial.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cargadora compacta • Elevador telescópico
Industrial: Cargadora compacta • Elevador telescópico

| | |
|-----------|-----------------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 400/80 R 24 IND (16.0/80 R 24) |
| LI/SS | 162 A8/B |

Dimensions International Standard

| | |
|----------------------------|---------------------------|
| Section Width (mm) | 404 |
| Overall Diameter (mm) | 1250 |
| Static Loaded Radius (mm) | 553 |
| Rolling Circumference (mm) | 3778 |
| SRI (mm) | 600 |
| Rim Rec | DW 13 |
| Rim Alt | DW 12 ; DW 13 L ; DW 14 L |
| ECE | E11-106R-002965 |

Load capacity (Kg)

| km/h / bar | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.4 | 3.6 | 4.0 | 4.4 | 4.6 | 4.8 | 5.0 | 5.2 | 5.4 |
|------------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 50 | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750 | - | - |
| 40 | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750 | - | - |
| 30 | 1985 | 2340 | 2750 | 3105 | 3460 | 3590 | 3770 | 4170 | 4515 | 4745 | 4860 | 5085 | - | - |
| 25 | 2060 | 2430 | 2850 | 3220 | 3590 | 3725 | 3910 | 4330 | 4690 | 4925 | 5040 | 5275 | - | - |
| 10 Cyc. | 2280 | 2785 | 3280 | 3850 | 4350 | 4600 | 4845 | 5280 | 5845 | 6090 | 6330 | 6655 | 6810 | 7125 |
| Static | 3500 | 4270 | 5030 | 5900 | 6670 | 7050 | 7430 | 8100 | 8960 | 9340 | 9710 | 10205 | 10445 | 10925 |

Printed on 04/05/2024 18:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..