

## MULTIMAX MP 540 - Especificaciones técnicas



### Description

BKT ha diseñado MULTIMAX MP 540 para todos los vehículos multiuso. Gracias a la carcasa All Steel, MULTIMAX MP 540 permite llevar cargas pesadas dentro y fuera de la carretera. Además, su diseño de patrón de bloques ofrece una estabilidad y una durabilidad excepcionales.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Vehículo universal

Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	275/80 R 20 (10.5 R 20)
LI/SS	134 K

## Dimensions US Standard

Usa code	94071357
Overall Width (inch)	10.6
Overall Diameter (inch)	37.6
Static Loaded Radius (inch)	17.4
Rolling Circumference (inch)	114.7
Rim Rec	W9
Rim Alt	9
ECE	E11-54R-0020628

## Load capacity (lbs)

mph / psi	75
68	4675

Printed on 18/05/2024 23:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..