

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	425/55 R17
LI/SS	129 D/140 A8

Dimensions International Standard

Section Width (mm)	420
Overall Diameter (mm)	894
Static Loaded Radius (mm)	397
Rolling Circumference (mm)	2704
SRI (mm)	425
Rim Rec	13.00
ECE	E11-106R-005104

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	595	760	945	1075	1240	1410	1540	1685	1850
50	720	920	1145	1300	1505	1705	1860	2040	2240
40	800	1025	1275	1450	1675	1900	2075	2275	2500
30	895	1150	1430	1625	1875	2125	2320	2545	2795
25	940	1200	1495	1700	1960	2225	2430	2665	2925
10	1070	1370	1700	1935	2235	2535	2765	3035	3330

Printed on 04/05/2024 21:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..