

## RIDEMAX FL 693 M - Especificaciones técnicas



### Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	650/50 R 22.5
LI/SS	163 D/160 E

## Dimensions US Standard

Usa code	94043019
Section Width (inch)	25.4
Overall Diameter (inch)	48.1
Static Loaded Radius (inch)	21.1
Rolling Circumference (inch)	146.3
Rim Rec	AG 20.00
ECE	E4-106R-001417

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3630	4070	5060	5750	6650	7540	8230	9030	9920
40	3920	4410	5490	6240	7210	8170	8930	9790	10750
30	4750	5330	6640	7550	8720	9890	10800	11840	13010
25	5350	6000	7460	8490	9800	11110	12140	13300	14620
15	6210	6970	8660	9850	11390	12920	14110	15460	16990
5	7070	7940	9880	11220	12960	14700	16060	17610	19340

Printed on 04/05/2024 15:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..