

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	169 D

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1389
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4216
SRI (mm)	650
Rim Rec	AG 20.00
ECE	E4-106R-000806

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1965	2230	2705	3130	3605	4085	4400	4880	5300
65	2150	2440	2960	3425	3945	4470	4815	5340	5800
50	2600	2950	3585	4145	4775	5410	5830	6460	7020
40	2920	3315	4025	4660	5370	6080	6550	7260	7890
25	3395	3850	4675	5410	6235	7060	7610	8435	9165
10	3865	4385	5325	6160	7100	8040	8670	9605	10440

Printed on 04/05/2024 18:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..