

## RIDEMAX FL 693 M - Especificaciones técnicas



### Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Camión cisterna • Remolque

Version	HD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	179 D

## Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1383
Static Loaded Radius (mm)	606
Rolling Circumference (mm)	4217
SRI (mm)	650
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E11-106R-006008

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1765	2260	2825	3175	3670	4165	4590	5010	5505	6210	7055
65	1940	2480	3100	3490	4030	4575	5040	5505	6045	6820	7750
50	2345	3005	3755	4225	4880	5535	6100	6660	7320	8255	9380
40	2635	3375	4220	4745	5485	6220	6855	7485	8225	9280	10540
30	2930	3750	4685	5270	6090	6910	7610	8315	9130	10305	11705
25	3065	3920	4900	5515	6370	7225	7960	8695	9555	10780	12245
10	3490	4465	5580	6280	7255	8235	9070	9905	10885	12280	13950

Printed on 04/05/2024 21:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..