

RIDEMAX IT 696 - Especificaciones técnicas



Description

RIDEMAX IT 696 se caracteriza por un único dibujo de la banda de rodadura y una huella amplia que proporcionan un excelente agarre en la carretera, incluso en condiciones invernales. El neumático se presta especialmente para las actividades de los medios municipales y de mantenimiento, gracias a las óptimas características de velocidad y la carcasa robusta. El dibujo de la banda de rodadura ha sido desarrollado especialmente para los trabajos más pesados y garantiza una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	340/80 R 24 IND (12.4 R 24)
LI/SS	140 A8/135 D

Dimensions US Standard

Usa code	94033843
Section Width (inch)	13.5
Overall Diameter (inch)	45.4
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	135.6
Rim Rec	DW 11
Rim Alt	W 10 ; W 12 ; DW 10
ECE	E4-106R-002293

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	2260	2790	3260	3790	4280	4810
30	2440	3010	3530	4090	4610	5180
25	2590	3200	3750	4350	4910	5510
20	2690	3330	3900	4530	5100	5730

Printed on 18/05/2024 23:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..