

RIDEMAX IT 696 - Especificaciones técnicas



Description

RIDEMAX IT 696 se caracteriza por un único dibujo de la banda de rodadura y una huella amplia que proporcionan un excelente agarre en la carretera, incluso en condiciones invernales. El neumático se presta especialmente para las actividades de los medios municipales y de mantenimiento, gracias a las óptimas características de velocidad y la carcasa robusta. El dibujo de la banda de rodadura ha sido desarrollado especialmente para los trabajos más pesados y garantiza una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	360/80 R 20 IND
LI/SS	143D/147A8

Dimensions US Standard

Usa code	94071074
Section Width (inch)	14.1
Overall Diameter (inch)	42.7
Static Loaded Radius (inch)	19.2
Rolling Circumference (inch)	127.4
Rim Rec	11
Rim Alt	W 10 ; W 11 ; 12 ; W 12
ECE	E11-106R-007845

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58
40	2890	3490	4160	4630	4810	4990	5470	6010
30	3120	3770	4490	5000	5200	5390	5910	6490
25	3260	3940	4680	5220	5420	5630	6170	6780
20	3460	4190	4980	5560	5780	5990	6570	7210

Printed on 18/05/2024 17:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..