

## RIDEMAX IT 696 - Especificaciones técnicas



### Description

RIDEMAX IT 696 se caracteriza por un único dibujo de la banda de rodadura y una huella amplia que proporcionan un excelente agarre en la carretera, incluso en condiciones invernales. El neumático se presta especialmente para las actividades de los medios municipales y de mantenimiento, gracias a las óptimas características de velocidad y la carcasa robusta. El dibujo de la banda de rodadura ha sido desarrollado especialmente para los trabajos más pesados y garantiza una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/80 R 34 IND (18.4 R 34)
LI/SS	164 A8/159 D

## Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1632
Static Loaded Radius (mm)	728
Rolling Circumference (mm)	4894
SRI (mm)	775
Rim Rec	W 15 L
Rim Alt	W 16 L
ECE	E4-106R-002296

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	2055	2540	2975	3455	3895	4375
50	2210	2725	3195	3715	4185	4700
40	2350	2900	3400	3950	4450	5000
30	2445	3015	3535	4110	4630	5200

Printed on 18/05/2024 22:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..