

## RIDEMAX IT 696 - Especificaciones técnicas



### Description

RIDEMAX IT 696 se caracteriza por un único dibujo de la banda de rodadura y una huella amplia que proporcionan un excelente agarre en la carretera, incluso en condiciones invernales. El neumático se presta especialmente para las actividades de los medios municipales y de mantenimiento, gracias a las óptimas características de velocidad y la carcasa robusta. El dibujo de la banda de rodadura ha sido desarrollado especialmente para los trabajos más pesados y garantiza una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	500/70 R 24 IND
LI/SS	164A8/159D

## Dimensions US Standard

Usa code	94070244
Section Width (inch)	19.8
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	155.7
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E11-106R-007547

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58
40	3860	4730	5310	6270	7140	8010	8780	9640
30	4170	5110	5730	6780	7720	8650	9480	10420
25	4410	5400	6060	7160	8160	9150	10030	11020
20	4630	5680	6370	7530	8560	9610	10540	11570

Printed on 18/05/2024 19:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..