

RT 747 AGRO INDUSTRIAL - Especificaciones técnicas



Description

RT 747 AGRO INDUSTRIAL es un neumático radial agro-industrial idóneo para palas compactas y telescópicas. Los tacos extra anchos aseguran un agarre excelente y una extraordinaria estabilidad en las operaciones de levantamiento. El neumático ha sido proyectado con una mezcla particularmente resistente a los cortes y los desgarros. RT 747 AGRO INDUSTRIAL es la mejor respuesta para todas las operaciones agrícolas que en general requieren una versatilidad excepcional.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cargadora compacta • Elevador telescópico
Industrial: Cargadora compacta • Elevador telescópico

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 460/70 R 24 (17.5L R 24) |
| LI/SS | 159A8/156B |

Dimensions International Standard

| | |
|----------------------------|-------------------|
| Section Width (mm) | 465 |
| Overall Diameter (mm) | 1254 |
| Static Loaded Radius (mm) | 556 |
| Rolling Circumference (mm) | 3840 |
| SRI (mm) | 575 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 14 L ; DW 16 L |
| ECE | E11-106R-005105 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 |
|------------|------|------|------|------|------|------|------|-------|
| 50 | 1535 | 1890 | 2245 | 2560 | 2915 | 3265 | 3505 | 4000 |
| 40 | 1705 | 2100 | 2495 | 2845 | 3240 | 3630 | 3895 | 4375 |
| 30 | 1775 | 2185 | 2595 | 2960 | 3370 | 3775 | 4050 | 4550 |
| 25 | 1805 | 2225 | 2645 | 3015 | 3435 | 3850 | 4130 | 4640 |
| 10 Cyc | 2560 | 3150 | 3745 | 4270 | 4860 | 5445 | 5845 | 6565 |
| Static | 3920 | 4830 | 5740 | 6545 | 7450 | 8350 | 8960 | 10065 |

Printed on 04/05/2024 21:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..