

TR 387 - Ficha técnica



Description

TR 387 es un neumático agro-industrial, idóneo para los remolques que transportan la caña da azúcar y los compactadores. Este neumático se caracteriza por una elevada capacidad de carga y está disponible en diferentes versiones con el fin de satisfacer las exigencias específicas de los usuarios en términos de resistencia a los cortes y los desgarres, trabajos pesados y durabilidad. La versión "dual bead", de doble talón, es particularmente idónea para los tractores industriales y las operaciones de transporte con remolques.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Industrial: Compactador

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|-------------------------|----------------------|----------|--------|----|-------------------|------------------------------|-----|------|-----|------|-----|------|-----------------|
| 11.2 - 24 | STANDARD | R4 | 116 A6 | | W 10 | W 9 | 292 | 1075 | 496 | 3228 | | TL | E11-106R-006420 |
| 18.4 - 26 | HD | R3 | 152 A6 | 16 | DW 16 L | DW 15 L | 485 | 1450 | 635 | 4150 | | TL | |
| 18.4 - 26 | STANDARD | R3 | 142 A6 | 10 | DW 16 L | DW 15 L | 485 | 1450 | 635 | 4150 | | TL | E11-106R-004638 |
| 18.4 - 26 | STANDARD | R3 | 146 A6 | 12 | DW 16 L | DW 15 L | 485 | 1450 | 635 | 4150 | | TL | E4-106R-002718 |
| 23.1 - 26 | DUAL BEAD | R3 | 159 A6 | 16 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TL | |
| 23.1 - 26 | DUAL BEAD HD | R3 | 161 A6 | 18 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TT | |
| 23.1 - 26 | DUAL BEAD HD | R3 | 161 A6 | 18 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TL | |
| 23.1 - 26 | HD | R3 | 164 A6 | 12 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TL | E11-106R-003647 |
| 23.1 - 26 | HD DUAL BEAD SPECIAL | R3 | 161 A6 | 18 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TL | |
| 23.1 - 26 | STANDARD | R3 | 145 A6 | 8 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TL | E11-106R-003595 |
| 23.1 - 26 | STANDARD | R3 | 153 A6 | 12 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TL | E4-106R-002317 |
| 23.1 - 26 | STANDARD | R3 | 159 A6 | 16 | DW 20 B | | 592 | 1560 | 690 | 4688 | 750 | TL | E4-106R-002318 |
| 12.4 - 28 | STANDARD | R3 | 123 A6 | 8 | W 11 | W 9 ; W 10 | 325 | 1200 | 550 | 3576 | | TL | E11-106R-005277 |
| 16.9 - 28 | STANDARD | R3 | 135 A6 | 8 | DW 15 L | DW 14 L | 440 | 1400 | 630 | 4074 | | TL | E11-106R-005278 |
| 16.9 - 30 (14 - 30) | STANDARD | R3 | 137 A6 | 8 | DW 15 L | DW 14 L | 440 | 1450 | 655 | 4220 | | TL | E11-106R-005279 |
| 18.4 - 30 (15 - 30) | HD | R3 | 151 A6 | 14 | DW 16 L | DW 15 L | 475 | 1530 | 680 | 4395 | | TT | |
| 18.4 - 30 (15 - 30) | STANDARD | R3 | 139 A6 | 8 | DW 16 L | DW 15 L | 475 | 1530 | 677 | 4511 | | TL | |
| 620/75 - 30 (23.1 - 30) | DUAL BEAD | R3 | 161 A6 | 16 | DW 20 A ; DW 20 B | | 605 | 1675 | | | | TL | |
| 620/75 - 30 (23.1 - 30) | DUAL BEAD HD | R3 | 164 A6 | 18 | DW 20 A ; DW 20 B | | 605 | 1675 | 0 | 0 | | TL | |
| 24.5 - 32 | DUAL BEAD HD | R3 | 164 A6 | 16 | DH 21 | DH 21 B ; DH 21 H ; DH 21 HB | 625 | 1755 | 790 | 5226 | | TL | |

Printed on 18/05/2024 18:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..