

## V-FLEXA - Ficha técnica



### Description

V-FLEXA es un neumático radial específicamente proyectado para los remolques agrícolas. Es un producto Flotation de última generación equipado con tecnología VF, que permite transportar cargas pesadas tanto en el campo como por la carretera con una presión de inflado inferior al 30% respecto a la de un neumático estándar con las mismas dimensiones. Los cinturones de acero aportan una mayor resistencia a la carcasa contra las agresiones. V-FLEXA no sólo soporta cargas pesadas en total seguridad, sino que evita también la compactación del suelo gracias a la perfecta distribución del peso. Además, V-FLEXA ofrece óptimas propiedades de autolimpieza y durabilidad, así como una baja resistencia al rodamiento.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Remolque

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>VF 560/60 R 22.5</b>	STEEL BELTED	166 D			AG 16.00		555	1250	550	3756	600	TL	E11-106R-006763
<b>VF 600/55 R 26.5</b>	STEEL BELTED	167 D			AG20.00		615	1342	580	3986	650	TL	E11-106R-006017
<b>VF 600/65 R 26.5</b>	STEEL BELTED	172 D			AG20.00		615	1453	628	4377	700	TL	E11-106R-006624
<b>VF 650/55 R 26.5</b>	STEEL BELTED	171 D			AG 20.00		644	1389	591	4100	650	TL	E11-106R-006399
<b>VF 710/50 R 26.5</b>	STEEL BELTED	176 D	176 D	176 D	AG 24.00		727	1383	600	4193	650	TL	E11-106R-008833
<b>VF 750/45 R 26.5</b>	STEEL BELTED	176 D	176 D	176 D	AG 24.00		755	1349	585	4095	650	TL	E11-106R-008832
<b>VF 710/50 R 30.5</b>	STEEL BELTED	178 D	178 D	178 D	AG 24.00		727	1485	654	4511	700	TL	E11-106R-008831
<b>VF 750/60 R 30.5</b>	STEEL BELTED	187 D	187 D	187 D	AG 24.00		780	1678	728	5085	800	TL	E11-106R-008147
<b>VF 750/60 R 30.5</b>	STEEL BELTED	187 D	187 D	187 D	AG 24.00		780	1678	728	5085	800	TL	E11-106R-008147

Printed on 05/05/2024 8:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..