

XL GRIP (BHL) - Especificaciones técnicas



Description

XL GRIP (BHL) ha sido particularmente desarrollado para las cargadoras retroexcavadoras que se utilizan en las operaciones más difíciles de excavación, apisonado y carga. El dibujo no direccional de la banda de rodadura asegura una óptima tracción y estabilidad. La mezcla especial de la banda de rodadura se traduce en una excelente resistencia a los cortes y las laceraciones, prolongando la vida de la banda de rodadura.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Cargadora retroexcavadora

| | |
|-----------|------------|
| Version | INDUSTRIAL |
| Type | TT |
| Tyre Size | 14.9 - 24 |
| LI/SS | 145 A8 |

Dimensions US Standard

| | |
|------------------------------|------------------------|
| Usa code | 94045396 |
| Ply Rating | 12 |
| Section Width (inch) | 15 |
| Overall Diameter (inch) | 48.8 |
| Static Loaded Radius (inch) | 22.6 |
| Rolling Circumference (inch) | 143.5 |
| Rim Rec | DW 13 |
| Rim Alt | DW 11 ; DW 12 ; DW 13L |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 42 |
| 25 | 6400 |

Printed on 05/05/2024 5:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..