

## XL GRIP (L3) - Especificaciones técnicas



### Description

XL GRIP (E-3/L-3) es un neumático de telas cruzadas de base ancha (**wide**) desarrollado para palas cargadoras, que minimiza el riesgo de cortes y perforaciones en las operaciones de carga más pesadas. Este neumático asegura una excelente tracción, así como un ciclo de vida prolongado del producto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Pala cargadora  
OTR: Buldócer • Pala cargadora

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TL        |
| Tyre Size | 17.5 - 25 |

## Dimensions International Standard

|                                   |           |
|-----------------------------------|-----------|
| <b>Ply Rating</b>                 | 20        |
| <b>Overall Width (mm)</b>         | 435       |
| <b>Overall Diameter (mm)</b>      | 1345      |
| <b>Static Loaded Radius (mm)</b>  | 622       |
| <b>Rolling Circumference (mm)</b> | 3980      |
| <b>Rim Rec</b>                    | 14.00/1.5 |
| <b>TRA Code</b>                   | E3/L3     |

## Load capacity (Kg)

| km/h / bar | 4.00 | 5.75 |
|------------|------|------|
| 50         | 5000 | -    |
| 10         | -    | 8250 |

Printed on 04/05/2024 19:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..